



SMOOTH CONCRETE WALLS

FULL CONCRETE WALLS - INSULATED SANDWICH PANELS

In a very short space of time, this once mundane product has grown to become a fully fledged wall cladding in its own right that fits in perfectly with the current trend for plainer, timeless commercial premises.

Increasing use is being made of this natural building material even in the private sector – often in combination with aluminium, glass and wood.

CONDECO makes use of the latest additives and releasing agents.

After stripping, we put the walls into indoor storage at our company premises.

This is beneficial to the drying process.

Given that this process plays such an important role in determining the walls' final colour, CONDECO has devoted half of its production warehousing space to storage.

FULL CONCRETE WALLS

MAXIMUM LENGTH	10 m
MAXIMUM HEIGHT	3,8 m
THICKNESSES	10 , 12, 14, 16, 18, 20 and 25 cm
STANDARD REINFORCEMENT	5,5 kg/m
SPECIFICATIONS	inside surface levelled off by hand in a natural grey concrete colour

INSULATED SANDWICH PANELS

MAXIMUM LENGTH	6,5 m
MAXIMUM HEIGHT	3,8 m
THICKNESSES	18, 20 and 25 cm
INSULATION THICKNESSES	40 to 80 mm in PS, PU and PIR

SMOOTH CONCRETE

